



Revel Environmental Manufacturing Inc.

sales@remfilters.com (888) 526-4736 Lic. No. 857410

Northern California
 960-B Detroit Avenue
 Concord, California 94518
 P: (925) 676-4736
 F: (925) 676-8676

Southern California
 2110 South Grand Avenue
 Santa Ana, California 92705
 P: (714) 557-2676
 F: (714) 557-2679

**REVEL ENVIRONMENTAL MANUFACTURING, INC. (REM Inc.)
 TRITON BIOFLEX TRASH GUARDS for DROP INLETS (BFTG)**

	5 mm	Maximum - Flow Rate	Flow Rate - 50% Blocked	Total Bypass	TRASH Volume Capacity	Maximum - Flow Rate** w/ Hydrocarbon Option
	Mesh Req:	CFS	CFS	CFS	Cubic Feet	CFS
DROP INLETS						
Model:						
TR10 (8) BFTG***	Yes	1.6	0.8	6.92	5.9*	0.34
TR10 (16) BFTG***	Yes	3.2	1.6	6.92	11.8*	0.69
TR10 (32) BFTG***	Yes	6.4	3.2	6.92	23.8*	1.38
TR14 (8) BFTG***	Yes	2.59	1.29	9.5	5.68*	0.66
TR14 (16) BFTG***	Yes	5.18	2.59	9.5	11.2*	1.33
TR14 (32) BFTG***	Yes	10.36	5.18	9.5	22.4*	2.67
TR24 (17) BFTG***	Yes	10.75	5.37	32.32	12*	2.42
TR24 (34) BFTG***	Yes	21.5	10.75	32.32	24*	4.84

* Based on a 3' X 3' catch basin. Volume will increase or decrease depending upon size of catch basin.

** Hydrocarbon (Oil, grease, animal fats, etc.) removal is an optional media that can be combined with the Bioflex Trash Guards.

*** REM will use the cartridge system that maximizes each catch basins trash capture volume and flow rate.